

AEI HA-268 (8 Zones Alarm System)



AEI HA-268 8 Zones Alarm Control Panel with Auto Dialer

HA-268 is an auto-dialer alarm control panel with 8 hardware protection zones and 2 software zones for panic and duress alarms, which is designed for home and office protections. The system gives local alarm warnings as like the traditional alarm systems as well as sending voice message to 4 telephones of pre-set numbers when alarm occurs. The auto dialer is compatible with public telephone systems. The control panel comes with one control console for ready installation. Each HA-268 comes with one alarm control panel and one full feature master control console. Auxiliary control consoles can be purchased separately (S5269). Both types of consoles are back lighting and have the same function except the built-in microphone for message recording is not available on the auxiliary control console.

FEATURES FOR ALARM

- 8 Zones, Programmable for Instant, Delay (2 delay time available),
- 24 Hour Instant or 24 Hour Silent Alarm Reporting
- Programmable Master Code and 8 User Codes
- All User Codes with Duress Function
- Protection Zones are Programmable for Single or Multiple Triggering
- Programmable Time for Exit, Entry (2 timings) and Alarm Duration
- Arm-Disarm Control from Keypad or Remotely from Any DTMF Telephone mobile Phone
- Each Protection Zone is Programmable for Response Time
- Exit and Entry Warning Beeps On-Off Options
- Arm-Disarm Ring Back Indication On-Off Options
- Instant Arming Codes for Home and Away Operations
- Built-in Dynamic Battery Charger and Tester with Auto or Manual Testing Options
- Two On Board Software Zone for Panic and Duress Alarms
- Maximum 4 Control Keypads Can Be Connected
- Home or Away Operation
- Forced to Arm or Arm Prohibited Options

AEI HA-268 (8 Zones Alarm System)

- Handover Option for the Instant Zones
- Facilities for Driving Siren/Bell, Satellite Siren and Strobe Light
- Power Low Watchdog Resets System
- Non-Volatile Memory
- Can be Arm-Disarmed by Conventional Key Switch
- Full Feature Default Values in System for Ready Use
- 12V / 6.5Ah Back-up Battery (Not Included)
- 16VAC Operation
- Weight: 2.2 Kg (The Control Panel); 220 g (The Keypad)
- Dimensions: 268(H) X 263(W) X 78(D) mm (The Control Panel); 117(H) X 117(W) X 27(D) mm (The Keypad)

FEATURES FOR AUTO-DIALER

- Four 32 Digit Telephone Numbers for Auto-Dialer
- Two 32 Digit Telephone Numbers for Communicator
- Communicator Data in DTMF Format with Check-sum
- Tone or Pulse Dialing
- Programmable Pause Time between Any Digits
- Voice Message and Numeric Message are Possible
- 20 Seconds Non-Volatile User Programmable Voice Message
- Controllable Listen-in Duration
- Back-up or Non-back-up Dialing for Alarm Reporting
- Automatic Telephone Line Fault Detection
- Programmable Dialing Attempts, 8 Maximum
- Programmable Message Repeats, 8 Maximum
- Telephone Numbers can be Tested Individually