



- ◆ Support 4CH/8CH Full HD IP Camera
- ◆ Up To 4CH/8CH Simultaneously Live Display / Playback
- ◆ Directly Configure NVR, Additional Personal Computer Is Not Required.
- ◆ Support Local Display, 1920x1080 Resolution
- ◆ Access through Web, CMS, Mobile APP
- ◆ Smart Recording, Optimize The Recording Efficiency Of HDD

SPECIFICATIONS

System	LNVR-4HD	LNVR-8HD
Operating System	Embedded Linux	
Operations	Live, Recording, Playback, Backup & Remote access	
Control Mode	USB mouse, IR remote control, Webpage, CMS	
Video		
Decompression	MPEG4, H.264 HP/MP/BP, up to 1080p30	
IP Camera Inputs	4 channel; each one is up to 1080p30	8 channel; each one is up to 1080p30
Audio		
Input	1 x RCA	
Output	1 x RCA	
2-way Audio	Support	
Display		
Display mode	Full screen/Multi-screen/PIP/Sequence	
Output	1x HDMI(1920x1080p60), 1xVGA(up to 1920x1080, 60Hz)	
Sequence	Support	
OSD	GUI	
Recording		
Recording Mode	Continuous, manual, scheduled, alarm, motion	
Recording Capability	Up to 120 fps at Full HD (1920x1080)	Up to 240 fps at Full HD (1920x1080)
Pre Recording	5 seconds	
Post Recording	300 or above seconds	
Playback & Backup		
Display mode	Full screen/Multi-screen	
Playback capability	4 channel simultaneous playback	8 channel simultaneous playback
Playback control	Play/Pause/Step/Fast forward/Rewind/Fast rewind	
Search Control	By Date/Time, Events	
Export	Through USB/Webpage	
Mobile Viewing on Smartphone/Tablet PC	Yes ; iOS, Android	
Internal Storage	2 x SATA Ports	

SPECIFICATIONS

	LNVR-4HD	LNVR-8HD
Network		
Support	TCP/IP,SMTP,DHCP,DDNS,PPPoE,UDP,SSL,RTP,RTSP,NTP	
Ethernet	1x10/100Mbps(WAN), 1x10/100/1000Mbps(LAN)	
I/O		
USB	2; 1 for mouse control and 1 for backup	
Alarm	4 Alarm in/ 1 Alarm out	8 Alarm in/ 2 Alarm out
RS485	1; Support Pelco D, Pelco P,Samsung and Transparent	
Security		
Watermark	Yes	
User Privilege	3 Levels of User Access Support	
Environmental		
Power	12V DC	
Dimension	320(W)x210(D)x50mm(H)	
Temperature	0°C ~ 40°C	
Weight	1.5KG	

CONNECTION DIAGRAM

